



TITAN SUPER GT

High-performance, gasoline engine passenger cars oil

Description

TITAN SUPER GT is premium quality multi-grade oil for Gasoline Engines with and without Turbo charging. It meets service requirements of the API Engine Service Classification SL., TITAN SUPER GT 20W-50 and 10W-30 bear API donut. They are also certified by Saudi Arabian Standard Organization (SASO) and bears a SASO quality seal.

Advantages/Benefits

- Improved high temperature deposit control resulting in longer engine life and better turbo-charge performance
- Excellent protection against wear due to improved lubrication film even at full-throttle operations
- Protects against Bore Polishing
- Optimise function of Hydraulic Tappets with no foaming.
- Protects against sludge formation
- Compatible with gaskets and seals.

Application

TITAN SUPER GT is recommended for year round use in passenger cars, light duty trucks and vans with naturally aspirated or turbocharged gasoline engines. It can also be used in light duty diesel engines,

Specifications

- API SL/CF

Follow the equipment manufacturer's recommendations for required lubricant performance levels and viscosity grades.

TITAN SUPER GT is available in three different viscosity grades TITAN SUPER GT 20W-50, TITAN SUPER GT 10W-40 and TITAN SUPER GT 10W-30 to meet all new advanced engines requirement

CHARACTERISTICS

TITAN SUPER GT 10W-30

Density @ 35 °C	0.868	g/ml	ASTM D 4052
Flash Point, CoC	226	°C	ASTM D 92
Pour Point	-33	°C	ASTM D 97
Kinematic Viscosity @ 40 °C	73.4	mm ² /s	ASTM D 445
Kinematic Viscosity @ 100 °C	11.20	mm ² /s	ASTM D 445
Viscosity Index	144	-	ASTM D 2270

Product Code 113 - 15/03/2011 Page 1

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product

ALHAMRANI FUCHS PETROLEUM SAUDI ARABIA LIMITED

P. O. Box 7103, Jeddah 21462, Saudi Arabia

Telephone +966 2 6635 666 FAX +966 2 6634 094 www.fuchs.com.sa

ISO 9001:2008
ISO 14001:2004
CERTIFIED





TITAN SUPER GT 10W-40

Density @ 35 °C	0.868	g/ml	ASTM D 4052
Flash Point, CoC	220	°C	ASTM D 92
Pour Point	-33	°C	ASTM D 97
Kinematic Viscosity @ 40 °C	104	mm ² /s	ASTM D 445
Kinematic Viscosity @ 100 °C	15.30	mm ² /s	ASTM D 445
Viscosity Index	155	-	ASTM D 2270

TITAN SUPER GT 20W-50

Density @ 35 °C	0,879	g/ml	ASTM D 4052
Flash Point, COC	246	°C	ASTM D 92
Pour Point	-24	°C	ASTM D 97
Kinematic Viscosity @ 40 °C	166	mm ² /s	ASTM D 445
Kinematic Viscosity @ 100 °C	18.9	mm ² /s	ASTM D 445
Viscosity Index	129	-	ASTM D 2270

