

Renolin Therm P 32

Product Code: 430A (Rev. 0 – 07 / 14)

Description

Renolin Therm P 32 is a highly refined; hydro-treated mineral oil designed primarily for use in closed loop heat transfer systems. Renolin Therm P 32 is designed for use in systems that are equipped with expansion tanks, and it is recommended to have pressure relief valves and an inert gas blanket on the system. In properly designed systems it will provide trouble free, long lasting service.

Application

Fuchs Renolin Therm P 32 has high specific heat and thermal conductivity at all temperatures and

therefore, will give rapid heating and efficient operation of the heat transfer system.

The application limits of heat transfer oils depend first on circulating speed and second on temperature in closed circuit systems. In general, the minimum velocities vs. temperatures are as follows:

- Velocity of 1.5 m/s (5 ft/s) for operating temperatures below 200°C (400°F).
- Velocity of 2.0 m/s (7 ft/s) for operating temperatures between 200 and 260°C (400 and 500°F).
- Velocity of 3.0 m/s (10 ft/s) for operating temperatures between 260 and 300°C (500 and 575 °F).
- Velocity of 3.5 m/s (12 ft/s) for operating temperatures above 300°C (575 °F).

Properties	Unit		Test Method
ISO Viscosity Grade		32	
Viscosity @ 40 °C	mm ² /s	32.6	ASTM D-445
@ 100 °C	mm ² /s	5.85	ASTM D-445
Viscosity Index	-	124	ASTM D-2270
Sp.Gr @85/85 °F	g/cm ³	0.8451	ASTM D-4052
Flash Point	°C	230	ASTM D-92
Pour Point	°C	- 27	ASTM D-97
Neutralization Number	mg KOH/g	0.03	ASTM D-974
Thermal Expansion Coefficient, 0-300 °C	1/K	0.000788	-
Thermal Conductivity @ 38 °C	W/m/K	0.126	-
Specific Heat @ 25 °C	J/Kg/K	1910	-

Product Code 430A – 17/07/2014. Page 1

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product

HASCOL PETROLEUM LIMITED

Suite # 105-106, "The Forum" G-20, Khayaban-e- Jami, Block-9, Clifton, Karachi-75600

UAN: 111-757-757, Tel: 021-5301343-50, Fax: 021-53013

e-mail: info@hascol.com

Web: www.hascol.com