

Normal climate

Heat transfer oil

- 10 **General application** Heat Transfer Oil for boiler or electric heater.
16 **Property** Heat transfer oil consists of highly refined paraffinic base stocks with good anti oxidation properties.
6 **General requirement** The heat transfer oil must be able to work at temperatures up to 300 °C.

Heat transfer oil

7175 ISO VG 32

Designation acc. to:

DIN 51502, Q
ISO 6743-12, QC
ANSI_AGMA -

Requirements acc. to:

DIN 51522, Q
ISO 6743-12, QC
ANSI_AGMA -

0 **Standard product**

Oil company name

Brugarolas
Carl Bechem, GmbH
Castrol
Engen Petroleum
FUCHS LUBRITECH
India Oil Corporation
Kuwait Petroleum
Mobil
Shell
Statoil
Texaco/Chevron/Caltex
Total

Product name

Beslux Term
BECHEM Staroil HTO 32
Perfecto HT 5
Genheat 32
RENOLIN THERM 330 S
Servotherm special
Q8 Gluck S
Mobiltherm 605
Shell Heat Transfer Oil S2
ThermWay
Texatherm 32
SERIOLA ETA 32

Comments on product

See temperature related design data in Shell TDS

Department

731 Oil preconditioning department

1

Local Control Panel

1

Process oil

Type
Volume

HT-32
29 m³

6,340 SSS
200 SSS
25,000 BSS