



TITAN ATF 3000

Universal DEXRON II (D) ATF for all automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation.

Description

TITAN ATF 3000 is an Automatic Transmission Fluid (ATF) performance level DEXRON II (D) and thus suitable for a large variety of applications. It is formulated on selected mineral base-oils and offers safe operation even under high stress in automatic transmissions, power steering systems and other hydraulic systems.

Application

TITAN ATF 3000 is miscible and compatible with conventional branded ATFs. However, a complete oil change is recommended when converting to TITAN ATF 3000 in order to exploit the product's full benefits.

Advantages/Benefits

- Protects against wear, sludge, adhesions and corrosion and offers outstanding, shear-stable viscosity-temperature properties
- Capable of high thermal stress and does not prevent successfully from foam
- TITAN ATF 3000 is compatible with many seal materials

Specifications/Approvals

- MAN 339 Type V1
- MAN 339 Type Z1
- MB-APPROVAL 236.6
- VOITH 55.6335.XX (G 607)
- ZF TE-ML 02F, 03D, 04D, 14A, 17C

FUCHS Recommendations

- DEXRON II (D)
- ALLISON C-4
- CAT TO-2
- FORD MERCON
- FORD M2C185-A
- FORD M2C138-CJ
- FORD M2C166-H
- FORD M2C9010-A
- OPEL 19 40 700
- RENK-DOROMAT
- VOLVO
- VW
- ZF TE-ML 09, 11A



CHARACTERISTICS: TITAN ATF 3000

| | | |
|------------------------------|--------------|------------------------|
| Density at 15°C | DIN 51757 | 0.873 g/ml |
| Colour | Visual | Red |
| Flash Point, CoC | DIN ISO 2592 | 200°C |
| Pour Point | DIN ISO 3016 | -50°C |
| Foaming Tendency Seq. II | ASTM D 892 | 30/0 ml |
| Dynamic Viscosity at -40°C | DIN 51398 | 34,000 mPas |
| Kinematic Viscosity at 40°C | DIN 51562-1 | 39 mm ² /s |
| Kinematic Viscosity at 100°C | DIN 51562-1 | 7.5 mm ² /s |
| Viscosity Index | DIN ISO 2909 | 164 |

September 2008 GDUK Page 2 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.